














VAPOR PROOF JELLY JAR



PHOTOMETRY



SPECIFICATIONS

DESCRIPTION

- ▶ One sku for both celling mount and wall mount
- ▶ Excellent thermal management
- ▶ 5 year warranty

LISTINGS

- ▶ UL listed for wet locations
- ▶ IP65 rated
- ▶ Energy star

LED CHARACTERISTICS

- ▶ 50,000 hours rated average life
- ▶ CRI > 80
- ► CTT: 3000K/4000K/5000K

ELECTRICAL

- ▶ Input line voltage : 100-277V
- ▶ Power factor > 0.9

CONSTRUCTION

- ▶ All die-cast aluminum construction
- Minimize glare with frosted glass globe
- ▶ Operating temperature : -30°C ~ 50°C

Applications

- Securitylighting
- Doorway
- ▶ Scaffolding lighting
- Construction sites lighting
- Fire hydrants

PRODUCT NOMENCLATURE

Example: VTJ20/8XX/MV

VTJ20/8XX/MV

2 3 4

Vapor Proof Jelley Jay

Wattage: 20=20W

3 CRI: 8=80

CCT : 30K=3000K/40K=4000K/50K=5000K

MV: 100-277V

ltem	Specification	20 WATTS
General Performance	Input Power (W)	20
	Lumens Delivered @ 5000K (lm)	2000
	Efficacy(lm/W)	100
	CRI	>80
	Calculated Lumen Maintenance	>50,000 hours
	Color Temperature	300K/4000K/5000K
Electrical	Input Voltage	100-277V
	Power Factor	> 90%
Certification	Certification	cULus Listed, Energy Star
	Environment	Wet location rated, IP65
	Warranty	5 years
	Operating Temperature	-30°C - 50°C

















VAPOR PROOF JELLY JAR

Dimension







INSTALLATION

Wall Mounting






1. Hold the fixture to the mounting surface, and mark the position of screw holes.
2. Refer to diagram, drilling the hole at each marks.
3. Insert a plastic anchor (not included) into each hole





Refer to diagram, stripping the wires.
 Connect the wire with power input line in junction by (L=Black, N=White, G=Yellow/Green)





Ceiling Mounting













T:+86.519.86387008,86385801,86387015 F:+86.519.86391024 www.plusrite.com/info@pluslight.com